

CLAMP-ONE

Wireless digital clamp-on meter

- Maximum reading of 3999.
- Heavy duty test leads.
- ACA Measurement up to 1000A.
- Ohm, Diode, Continuity, Capacitance, Frequency and Duty input Protection to 750V DA/AC rms.
- Diode test and Audible continuity check function.
- Auto power off to preserve battery life.
- Display back-light feature.
- Provides DATA-HOLD, RELATIVE.
- Complete of external temperature probe.

Code	Model	Dimensions	Weight
09006008	CLAMP-ONE	225 x 97 x 40 mm	0,45 kg



Electrical specifications

	Range
DC voltage	400mV, 4V, 40V, 400V, 1000V
AC voltage	4V, 40V, 400V, 750V
DC current	200A, 1000A
AC current	400A, 1000A
Resistance	400Ω, 40KΩ, 400KΩ, 4MΩ, 40mΩ
Quantity	5124F, 5, 124F, 51.24F, 100 4F
Temperature	-20 to 1000 °C
Frequency	5.12Hz, 51.2Hz, 512Hz, 5.12kHz, 512kHz, 5.12MHz
Duty current	0.1% to 99.9%



Calibration

Code	Model	Description
09053017		Calibration report ref. Accredia for clamp-on meter
09006008001	CLAMP-ONE/CT	Clamp-on meter with calibration report

INDISPENSABLE FOR INVERTER UNITS CHECK



COMPATIBLE APPS WITH FOX-ONE



PHONE APP

